

# FLOR-TEC INC.

Phone: 570-655-8247

E-mail: sales@flor-tec.com

## Professional Polymer Applications Team High Performance Coating Systems

Prepared and Installed by Professionals

High Performance Coating Systems begin with proper surface preparation. At Flor-Tec, we use state of the art **shot blasting** and **surface grinding systems** to clean and produce mechanical profile. Next, penetrating primer is applied to insure maximum adhesion to your substrate.

All of our systems are designed as floor coatings, not just floor paint. Different types of polymers such as epoxy, polyurethane, polyaspartic and MMA are used to produce floor coating systems that last.



▶ 5 Standard levels of ant-slip provides safe work surfaces

▶ Smooth surface for dry easy to clean floors.

▶ **Bio-Pruf Antimicrobial** can be incorporated into most coating systems to prevent a broad spectrum of bacterial and fungal attacks.

▶ Cleans easily, saving detergent, labor and water.

▶ Complies with VOC regulations.

▶ **17 Standard Colors** and unlimited custom blends to choose from.



▶ Seals concrete, protecting against dirt and spills.

▶ Eliminates concrete dusting.

▶ Safety marking and custom graphics improve visibility of designated areas.



▶ Provides neat appearance and well kept look.

▶ Reduces maintenance compared to bare concrete.

▶ Coating systems are applied in thin film high build and self leveling versions. All our coating systems provide general to high chemical resistance.



▶ Coatings are applied over concrete, steel and wood surfaces.

▶ Elastic coating provides flexible and waterproof base coat for most finishes.

▶ Coatings are a good choice for plywood substrates; they protect and seal out moisture, and can be top coated with a variety of finishes.

▶ High performance urethane topcoats improve chemical and abrasion resistance.

▶ MMA Systems can be applied to -20 degrees Fahrenheit.

▶ Urethane formulations are available in high gloss, satin or flat finishes.



#### Optional items for coating systems

- ▶ **Crack and joint repairs**
- ▶ 5 Standard levels of anti-slip grit.
- ▶ **Monolithic cove base 2,4,6 inch.**
- ▶ **Concrete spall repairs.**
- ▶ Traffic lines and custom graphics.
- ▶ Moisture testing and remediation systems.
- ▶ Polyurethane and polyespartic topcoats.

**The possibilities and applications are almost endless.**

Call or e-mail us to discuss your flooring application needs with the dedicated and experienced polymer flooring professionals at Flor-Tec Inc.

Flor-Tec, Inc. P.O. Box 887 Pittston, Pa 18640 (570)-655-8247 or Sales@flor-tec.com