

FLOR-TEC INC.

Phone: 570-655-8247

E-mail: sales@flor-tec.com

Professional Polymer Applications Team

Epoxy Mortar Resurfacer

This heavy-duty seamless, trowel-applied resurfacer incorporates epoxy resins and specially graded aggregates. It is ideal for repair of slight to badly spalled or eroded substrates.

This system is also used for producing a heavy traffic chemical resistant floor surface on new concrete floors. Epoxy mortar is usually applied at a minimum of 3/16" to whatever thickness necessary to correct floor irregularities.

Epoxy mortar produces a 17,000 P.S.I. high strength and impact resistant floor.



- ▶ High impact and wear resistant - will be stronger than concrete surface.
- ▶ 2 to 3 times the strength of concrete.
- ▶ Urethane and Epoxy finish coats provide specific performance characteristics as needed.

▶ Textures - Smooth and 5 standard levels of slip-resistant aluminum oxide grit.

▶ Chemical resistant.

▶ Hand or power trowel applied.



▶ Avoid costly product damage due to cracked, spalled or rough concrete floors.

▶ Will not support growth of fungus or bacteria, when **Bio-Pruf** is used.

▶ USDA-accepted and no solvent odors.

Thermal Shock Resistant

▶When grouted and sealed, Epoxy mortar eliminates porosity and produces a dense, skid-inhibiting finish that will minimize dirt and chemical penetration.

Available in **17 standard colors.**



▶Designed to be an Industrial Floor System.

▶Resists changes in temperature, abrasion, and harsh cleaning chemicals.

▶Epoxy Resurfacers are capable of withstanding heavy duty traffic while improving safety.

▶Can be used to form an **integral cover base** where specified.



▶For a truly impressive, long-lasting economical alternative to replacing badly eroded and spalled concrete slabs.

▶Restore worn, pitted or deteriorated concrete to a smooth, highly dense surface with 100% solids epoxy mortar.

Call or e-mail us to discuss your flooring application needs with the dedicated and experienced polymer flooring professionals at Flor-Tec Inc.
Flor-Tec, Inc. P.O. Box 887 Pittston, Pa 18640 (570)-655-8247 or Sales@flor-tec.com