

FLOR-TEC INC.

Phone: 570-655-8247
E-mail: sales@flor-tec.com

Professional Polymer Applications Team

Seamless Quartz Flooring

They are as durable as they are decorative, made from colored quartz aggregates permanently fused with premium epoxy resins. Available in 3 standard textures with 2 sizes of aggregate engineered to resist deterioration as well as withstand a variety of elements.



▶ Bonds permanently to most types of sound substrates including concrete, quarry tile, brick pavers steel deck and plywood.

▶ Ideal for new construction as well as repair and restoration.

▶ Time tested formulations provide great looking tough, anti-slip sanitary, surface.

▶ Broadcast and trowel applications methods.

▶ Many stock and custom colors can create the look you desire.

▶ Chose from solid or multi color patterns with a decorative look. **Solid** color chart can be [viewed here](#) in a PDF format; **multi** color chart can be [viewed here](#) in a PDF format.



▶ Easy to maintain nonporous floor surfaces that meet or exceed USDA, FDA, EPA and OSHA standards.

▶ **Integral cove** creates seamless floors wall to wall.

▶ Resist thermal cycling from 32 F to 200 F without cracking.

▶Designed for a wide range of applications where slip resistance, ease of cleaning and appearance are major considerations

▶No open joints to harbor bacteria or dirt.

▶V.O.C. compliant.



▶Stain resistant.

▶Can be re-glazed to renew appearance.

▶Available in **BIO-PRUF** broad spectrum antimicrobial formulas.

Quartz Flooring Technical Data and physical properties available here.

The possibilities and applications are almost endless.

Call or e-mail us to discuss your flooring application needs with the dedicated and experienced polymer flooring professionals at Flor-Tec Inc.

Flor-Tec, Inc. P.O. Box 887 Pittston, Pa 18640 (570)-655-8247 or Sales@flor-tec.com

